Printing date 07/24/2023 Revised On 07/24/2023

1 Identification of the substance and manufacturer

Trade name: **HICKORY** RA20220007 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Manufacturer/Supplier: Seymour of Sycamore

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Eye Irritation 2A H319 Causes serious eye irritation.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**







GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
	Acetone	15-25%
	propane	15-25%
	Calcium Carbonate	10-15%
106-97-8		10-15%
	VM&P Naphtha	10-15%
	Mineral Spirits	5-10%
108-88-3		1-5%
	Isopropyl Alcohol	1-5%
108-65-6	PM acetate	1-5%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. of page 1)

Safety Data Sheet

Printing date 07/24/2023 Revised On 07/24/2023

Trade name: HICKORY

After swallowing:

Most important symptoms and

effects:

Indication of any immediate medical

attention needed:

Dizziness

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

Rinse mouth with water. Do not induce vomiting.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Methods and material for containment and cleaning up: Use respiratory protective device against the effects of fumes/dust/aerosol.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Time: end of shift

Parameter: Acetone (nonspecific)

Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store lockéd up.

8 Exposure controls/personal protection		
Components with limit values that require monitoring at the workplace:		
67-64-1 Acet		
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 590 mg/m³, 250 ppm	
TLV (USA)	Short-term value: 500 ppm	
	Long-term value: 250 ppm A4, BEI	
74-98-6 prop	vane	
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm	
TLV (USA)	see Appendix F Minimal oxygen content (D, EX)	
106-97-8 n-b	utane	
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm	
TLV (USA)	Short-term value: 1000 ppm (EX)	
108-88-3 Tol		
PEL (USA)	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
REL (USA)	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm	
TLV (USA)	Long-term value: 20 ppm BEI, OTO, A4	
67-63-0 Isop	ropyl Alcohol	
PEL (USA)	Long-term value: 980 mg/m³, 400 ppm	
REL (USA)	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm	
TLV (USA)	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4	
108-65-6 PM		
WEEL (USA)	Long-term value: 50 ppm	
Ingredients	with biological limit values:	
67-64-1 Acet	•	
BEI (USA) 25 mg/L		
Medium: urine		

(Contd. on page 3)

(Contd. of page 2)

Printing date 07/24/2023 Revised On 07/24/2023

Trade name: HICKORY

108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene
0.3 mg/g creatinine

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

67-63-0 Isopropyl Alcohol

BEI (USA) 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Store protective clothing separately. Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Solvent
Odor threshold: Not determined.

pH-value:
Melting point/Melting range
Boiling point:
Flash point:
Flammability (solid, gas):

Not determined.
Undetermined.
-44 °C (-47.2 °F)
-19 °C (-2.2 °F)
Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol % 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapor density Not determined.

Evaporation rate
Partition coefficient: n-octonal/water: Not determined.
Solubility:
Viscosity:
Not determined.
Not determined.
Not determined.

Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials:
Hazardous decomposition:

No further relevant information available.
No dangerous decomposition products known.

Printing date 07/24/2023 Revised On 07/24/2023

Trade name: HICKORY

(Contd. of page 3)

11 Toxicological information

LD/LC50 values that are relevant for classification:

67-63-0 Isopropyl Alcohol

Oral LD50 4,570 mg/kg (rat) LD50 13,400 mg/kg (rab) Dermal

Inhalative LC50/4 h 30 mg/l (rat)

108-65-6 PM acetate

LD50 8,500 mg/kg (rat) Oral Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available. No irritant effect. Skin effects: Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

solvents.

Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable ADR 1950 AEROSOLS

Transport hazard class(es):

2.1 Gases Class Special precautions for user: Warning: Gases F-D,S-U **EMS Number:**

Packaging Group:

UN "Model Regulation": **UN 1950 AEROSOLS, 2.1**

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

67-63-0 Isopropyl Alcohol

Toxic Substances Control Act

All hazardous ingredients are found on the inventory list of substances. (TSCA):

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

13463-67-7 titanium dioxide

1333-86-4 Carbon black

100-41-4 ethyl benzene

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

67-64-1 Acetone

16 Other information

Contact: Regulatory Affairs