Printing date 07/24/2023 Revised On 07/24/2023

#### 1 Identification of the substance and manufacturer

Trade name: **TILE RED** RA20220009 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:** 

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

# 2 Hazard(s) identification

#### Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Eye Irritation 2A H319 Causes serious eye irritation.

Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.

Toxic to Reproduction 1B H360 May damage fertility or the unborn child. Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms** 







GHS02 GHS04 GHS07 GHS08

Signal word Danger

**Hazard statements** Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

Suspected of causing cancer. Route of exposure: Inhalation.

May damage fertility or the unborn child. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use. **Precautionary statements** 

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. Chemical Description:

Chemical Description.		This product is a mixture of the substances listed below with normazardous additions.	
	components:		
67-64-1	Acetone		15-25%
	propane		15-25%
1317-65-3	Calcium Carbonate		10-15%
	n-butane		10-15%
	VM&P Naphtha		5-10%
	Mineral Spirits		5-10%
108-88-3			1-5%
	Isopropyl Alcohol		1-5%
	PM acetate		1-5%
13463-67-7	titanium dioxide		1-5%

### 4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. of page 1)

**Safety Data Sheet** 

Printing date 07/24/2023 Revised On 07/24/2023

Trade name: TILE RED

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water. After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Rinse out mouth and then drink plenty of water.

Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Indication of any immediate medical attention needed:

Dizziness

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:

Special hazards: Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

## 8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:						
67-64-1 Acetone						
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm					
REL (USA)	Long-term value: 590 mg/m³, 250 ppm					
TLV (USA)						
	Long-term value: 250 ppm A4, BEI					
74-98-6 prop	74-98-6 propane					
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm					
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm					
TLV (USA)	see Appendix F Minimal oxygen content ( D, EX)					
106-97-8 n-b	n-butane					
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm					
TLV (USA)	TLV (USA) Short-term value: 1000 ppm (EX)					
108-88-3 Tol	108-88-3 Toluene					
PEL (USA) Long-term value: 200 ppm						
	Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift					
REL (USA)	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm					
TLV (USA)	TLV (USA) Long-term value: 20 ppm BEI, OTO, A4					
	Isopropyl Alcohol					
PEL (USA)	Long-term value: 980 mg/m³, 400 ppm					
REL (USA)	REL (USA) Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm					
TLV (USA) Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4						

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 07/24/2023 Revised On 07/24/2023

Trade name: TILE RED

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine

Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

67-63-0 Isopropyl Alcohol

BEI (USA) 40 mg/L

Mediŭm: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

Keep away from foodstuffs and animal feed. Wash hands after use. Hygienic protection:

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Store protective clothing separately. Avoid contact with the eyes and skin.

Do not eat or drink while working.

**Breathing equipment:** A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be

worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance. Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. -44 °C (-47.2 °F) **Boiling point:** Flash point: -19 °C (-2.2 °F)

Flammability (solid, gas): Extremely flammable. **Decomposition temperature:** Not determined.

Product is not self-igniting. Auto igniting:

In use, may form flammable/explosive vapour-air mixture. Danger of explosion:

1.5 Vol % **Lower Explosion Limit:** 10.9 Vol % Upper Explosion Limit: Not determined. Vapor pressure:

Between 0.77 and 0.85 (Water equals 1.00) Relative Density:

Vapor density Not determined. Not applicable. **Evaporation rate** Partition coefficient: n-octonal/water: Not determined. Not determined. Solubility: Viscosity: Not determined.

Water: 0.0 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

(Contd. on page 4)

Safety Data Sheet

Printing date 07/24/2023 Revised On 07/24/2023

Trade name: TILE RED

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. No dangerous decomposition products known. Hazardous decomposition:

(Contd. of page 3)

# 11 Toxicological information

LD/LC50 values that are relevant for classification:

67-63-0 Isopropyl Alcohol

Oral LD50 4,570 mg/kg (rat) Dermal LD50 13,400 mg/kg (rab) Inhalative LC50/4 h 30 mg/l (rat)

108-65-6 PM acetate

Oral LD50 8,500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

13463-67-7 titanium dioxide

LD50 >20,000 mg/kg (rat) Oral Dermal LD50 >10,000 mg/kg (rbt)Inhalative LC50/4 h >6.82 mg/l (rat)

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

The product is degradable after prolonged exposure to natural weathering processes. Persistence and degradability:

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information:

solvents.

No further relevant information available. Bioaccumulative potential: No further relevant information available. Mobility in soil: Other adverse effects: No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty cans should be recycled. Recommendation:

14 Transport information

**UN-Number** UN1950 DOT UN1950 DOT DOT

Aerosols, flammable

ADR 1950 Aerosols

Transport hazard class(es):

Class 2.1 Gases Marine pollutant: No Warning: Gases Special precautions for user:

F-D,S-Ŭ **EMS Number:** 

Packaging Group: UN "Model Regulation": UN1950, Aerosols, 2.1

## 15 Regulatory information

#### SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

# SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

67-63-0 Isopropyl Alcohol

**Toxic Substances Control Act** 

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

All ingredients are listed or exempted. (DSL):

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

(Contd. on page 5)

# Safety Data Sheet

Printing date 07/24/2023 Revised On 07/24/2023

Trade name: TILE RED	
California Proposition 65 chemicals known to cause cancer:	(Contd. of page 4)
13463-67-7 titanium dioxide  100-41-4 ethyl benzene	
Prop 65 chemicals known to cause birth defects or reproductive harm:  108-88-3   Toluene	
EPA: 67-64-1   Acetone	

# **16 Other information**

Contact: Regulatory Affairs