

# W20 Synthetic Underlayment



## FEATURES - COMPLIANCE: CODES

- Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV
- Performance characteristics meet or exceed ASTM D226 – Type I, II
- Meets the requirements of ICCAC-188 – Intertek / WH #CCRR 1115
- Ultraviolet Exposure –30 days
- ASTM E108 – Class A Fire – Passed
- ASTM D6757 –Inorganic Shingle Underlayment Standard
- UL Classified as a Prepared Roofing Accessory
- Limited Warranty –20 years

## CAUTIONS: SAFETY FIRST

As with any roofing product, always learn and follow safe roofing practices according to OSHA and local building code requirements and use and wear proper fall protection devices when working on roofs. Always use caution when walking on sloped roof decks and CraftGrade W20 underlayment as slip resistance may vary with surface conditions, weather, footwear and roof pitch. Do not walk on unsecured CraftGrade W20 or any other loose roofing material lying on sloped roof decks. Dust, dew, water or debris creates unsafe conditions on the roof. The presence of any foreign material may drastically change the coefficient of friction (traction) on CraftGrade W20 or any other material on a sloped roof deck. Failure to always use proper safety equipment and footwear can result in serious injury or even death.

## COMPLIANCE: CODES

- Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV
- Performance characteristics meet or exceed ASTM D226 – Type I, II
- Meets the requirements of ICC-AC-188 – Intertek / WH #CCRR 1115
- Ultraviolet Exposure – 30 days
- ASTM E108 – Class A Fire – Passed
- ASTM D6757 – Inorganic Shingle Underlayment Standard
- UL Classified as a Prepared Roofing Accessory
- Limited Warranty – 20 years

### PHYSICAL DATA

ROLL SIZE	48" X 250'
MATERIAL PER ROLL	1,000 sq. ft.
SQUARES PER ROLL	10 squares
WEIGHT PER ROLL	19 lbs

PRODUCT NUMBER: **TOP1SGWWTSCGW20**

Made in India



Scan QR Code  
for additional  
information.