



FEATURES + BENEFITS

- Premium, All-Weather, All-Season Flashing Cement
- For the Professional Contractor
- Heavy-Duty, Rubberized Providing Strong Adhesion to Wet and Dry Surfaces
- Bonds Underwater for Permanent Repairs
- Repairs Splits, Seams, Cracks and Holes in Spudded Gravel, Mineral Surfaced Cap Sheet, Smooth Surface Asphalt Roofs, Most App Granulated and SBS Membranes and Shingle Roofs
- Superior High Temperature Resistance

AVAILABLE SIZES



APPROVAL CODES



PHYSICAL PROPERTIES	
Maximum V.O.C.	< 250 g/L
Consistency	Thick mastic
WPG (Nominal)	8.7 lbs. per gal
Flash Point (TCC)	105° F +
Service Temp	45°F +
Resistance to Acids/Alkyds	Excellent

KEEP OUT OF REACH OF CHILDREN. Close container after each use. DO NOT TAKE INTERNALLY! If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY!

To the best of our knowledge, all technical data contained herein is true and accurate as of the date of the issuance and subject to change without prior notice. User must contact TROPICAL ROOFING PRODUCTS (TRP) to verify correctness before specifying or ordering. We guarantee our product to conform to the quality control standards established by TRP. We assume no responsibility for coverage, performance or injuries resulting from use. Liability if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY TRP EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

DESCRIPTION: TopSpec™ “best-in-class” #2100 All Weather Rubberized Flashing Cement is specifically formulated for the professional roofer providing strong adhesion to wet and dry surfaces. Will bond under water for permanent repairs. #2100 All Weather Rubberized Flashing Cement is manufactured with superior oxidized asphalts for extreme durability. With its high SBS rubber content and fortified with Power Gel Technology, #2100 will remain highly resilient, flexible, and durable through all seasons. Special surfactants make this product adhere to most surfaces in wet or dry conditions. #2100 All Weather Rubberized Flashing Cement is the premier repair compound that is easily spread and applied to repair splits, seams, cracks and holes in spudded gravel, mineral surfaced cap sheet, smooth surface asphalt roofs, and most APP and SBS membranes. It will seal areas around skylights, chimneys, vent pipes, gravel guards, down spouts, cracks in concrete and control joints on roofs. This product is an excellent utility mastic for use below grade. Will not run, slip, sag, or mud crack. Recommended for flat commercial roofs, in locations where roof is exposed to high heat and is excellent for repairs on conventional BUR membranes where movement is expected to occur. **RECOMMENDED SUBSTRATE APPLICATION - APP GRANULAR MEMBRANE, TORCH DOWN, TILE & METAL. NOT RECOMMENDED FOR SHINGLES.** Meets ASTM D 4586 and ASTM D 3409. Miami-Dade NOA Compliant.

PREPARATION: Surface must be clean and free from rust or any other foreign matter that would interfere with a good bond. For best results in cold weather, store at room temperature for 24 hours prior to application.

Application Methods



Application rate of approximately 40 linear feet per gallon with 4" wide 1/8" thick application. Application rates will vary by surface, porosity, and job conditions. Please consult Tropical Roofing Products for total dry film thickness requirements.

APPLICATION: Use a trowel, putty knife, or gloved hand to repair cracks, tears, holes, and breaks by applying cement 1/8" to 1/4" thick. Apply and work cement into break or crack, then apply cement 2"—4" beyond the problem area feathering the edges. Embed fabric to reinforce cement, then cover with additional cement, if problem area is over 1/4" wide or 2" long.

COVERAGE: Application rate of approximately 40 linear feet per gallon with 4" wide 1/8" thick application. NOTE: DO NOT use on APP, TPO, EPDM, PVC

CLEANUP: Clean tools with mineral spirits or paint thinner.

STORAGE & PRECAUTIONS: DO NOT ALLOW TO FREEZE. DO NOT THIN. DO NOT HEAT CONTAINER or store at temperatures greater than 120°F. Be sure the lid is tight and the pail is secured when transporting this product. Do not allow pail to tumble as this may loosen the lid and allow leakage or spillage to occur.

CLEAN-UP: Clean tools with xylene. throughout the United States. Check with your local representative for product availability.

Scan the QR code
to access additional
information

