



# SHINGLE & FLASHING AEROSOL

## Roof Accessory Paint



TopShield® Shingle & Flashing Roof Accessory Paint is a fast drying aerosol enamel with built-in corrosion protector used to hide flaws, blemishes, and unsightly roof protrusions. It provides superior protection, durability, and adhesion.

### FEATURES

- Adds the final touch with a professional finish
- Hides flaws, blemishes, and unsightly protrusions
- Provides a smooth, durable, rust fighting finish that prevents stains
- Dries in 8 minutes or less

### FOR USE ON

- ▶ Asphalt shingles, aluminum, metal, PVC, other plastics and more

### SURFACE PREPARATION:

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log onto [www.epa.gov/lead](http://www.epa.gov/lead). Surface should be clean, dull & dry. Remove loose rust & paint with the wire brush or sandpaper.

### PAINTING CONDITIONS:

Spray outdoors or in a well-ventilated area. Protect surrounding areas. Best results are achieved when air and surface temperature are between 40-80°F. For best results, do not use in high humidity. **DO NOT PAINT OBJECTS WHILE THEY ARE HOT.**

### APPLICATIONS:

Shake can for 2 minutes after ball within begins to rattle. Continue to shake for 10 seconds after each minute of use. Test spray in an inconspicuous area for compatibility. Hold can 8-12" from surface, spray in sweeping motion side to side with slight overlap. Apply multiple thin coats.

### COVERAGE:

Approximately 25 sq. ft.

### DRY TIME:

Dry to touch in 8 minutes. Tack free in 15 minutes. Apply additional coats within 2 hours or after 8 hours.

### AFTER USE:

To prevent clogs, hold can upside down and spray until clear gas appears. To clean paint on actuator, wear eye protection and wipe off with lacquer thinner-DO NOT stick pin in opening. Recycle empty can per local regulations.

### STORAGE LIFE:

Three years

ITEM CODE	SIZE	DESCRIPTION	QTY
TS0383101	12 oz	TOPSHIELD® ROOF ACCESSORY PAINT – Black	6/Case
TS0383132	12 oz	TOPSHIELD® ROOF ACCESSORY PAINT – Charcoal	6/Case
TS0383133	12 oz	TOPSHIELD® ROOF ACCESSORY PAINT – Dark Gray	6/Case
TS0383134	12 oz	TOPSHIELD® ROOF ACCESSORY PAINT – Deep Brown	6/Case
TS0383104	12 oz	TOPSHIELD® ROOF ACCESSORY PAINT – Brown	6/Case
TS0383108	12 oz	TOPSHIELD® ROOF ACCESSORY PAINT – Cedar	6/Case
TS0383131	12 oz	TOPSHIELD® ROOF ACCESSORY PAINT – Slate	6/Case
TS0383135	12 oz	TOPSHIELD® ROOF ACCESSORY PAINT – Terra Cotta	6/Case
TS0383102	12 oz	TOPSHIELD® ROOF ACCESSORY PAINT – Weathered Wood	6/Case



White  
TS0383101



Charcoal  
TS0383132



Dark Gray  
TS0383133



Deep Brown  
TS0383134



Brown  
TS0383104



Cedar  
TS0383108



Slate  
TS0383131



Terra Cotta  
TS0383135



Weathered Wood  
TS0383102



# SHINGLE & FLASHING AEROSOL

## Roof Accessory Paint

CONTAINS KETONES AND TOLUENE. DANGER! EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE -Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. CONTENTS UNDER PRESSURE. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water, and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. VAPOR HARMFUL. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. SEE SAFETY DATA SHEET. DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

### PERFORMANCE TESTING:

Technical data furnished herein is accurate and true to the best of our knowledge. However, no guarantee of accuracy is express or implied. We assume no responsibility or liability as a result of purchase, coverage, application, or injuries resulting in misuse.

### LIMITED WARRANTY:

If when applied according to label directions this product fails to perform in accordance with its published literature, upon satisfactory evidence of product failure, and as your sole remedy, we will either replace the product at no cost or refund the original purchase price. Labor or costs associated with labor are not included. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY, WHICH ARE ALL DISCLAIMED AND/OR LIMITED IN DURATION TO THE EXTENT PERMITTED BY LAW. WE SHALL NOT BE LIABLE FOR INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES (INCLUDING LOST PROFITS) FROM ANY CAUSE WHATSOEVER AND SUCH DAMAGES ARE EXPRESSLY EXCLUDED. Some states do not allow the exclusion or limitation of incidental or consequential damages or how long an implied warranty lasts, so the above limitation or exclusion may not apply to you. This limited warranty gives you specific legal rights, and you may also have other rights that vary from state to state.

### DANGER:

Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations



Scan the QR code to access additional information.