

# HouseWrap - PLUS

Polypropylene Weather Resistant Barrier

**TopShield® HouseWrap-PLUS** is a tear resistant woven and coated polypropylene weather resistant barrier that provides air and moisture protection. **TopShield® HouseWrap-PLUS** is manufactured with great translucency for easier on stud installation without the need for nailing marks and offers tear strength that will withstand the rigors of the job site and weather elements.

**TopShield® HouseWrap-PLUS** is manufactured from a polypropylene woven fabric with a polypropylene coating that contains UV inhibitors.

## PRODUCT FEATURES & BENEFITS

- Provides protection from water infiltration but breathes allowing water vapor to escape through micro perforations offering protection to the interior wall cavity
- Custom printing for as little as one pallet
- UV resistant and can be left exposed for up to 6 months
- Tear resistant reduces jobsite waste and blow-offs
- Meets and exceeds all current building codes for water resistive barrier as well as air barrier

PRODUCT SPECIFICATIONS		TEST METHOD		ROLL SIZE	ROLLS PER PALLET
Composition	Woven Polypropylene			9' x 100'	50
Weight Per Roll	14.4 lbs./MSF			9' x 150'	45
Thickness	6.5 mils.			9' x 195'	40
Tensile Strength	MD	60	ASTM D-828	10' x 100'	50
	CD	44		10' x 150'	45
Tear Strength	MD	34	ASTM D-4533	10' x 195'	40
	CD	30		54" x 100'	100
Water Resistance	Pass		ASTM D-779	54" x 150'	90
MVTR/Perms	9 Perms		ASTM E-96	54" x 195'	80
Fire Rating	Class A		ASTM E-84	36" x 100'	150
				36" x 150'	135

Scan the QR code  
to access additional  
information.

