

HouseWrap

Polypropylene Weather Resistant Barrier

TopShield® HouseWrap is a tear resistant woven and coated polypropylene weather resistant barrier that provides air and moisture protection. **TopShield® HouseWrap** is manufactured with great translucency for easier on stud installation without the need for nailing marks and offers tear strength that will withstand the rigors of the job site and weather elements.

TopShield® HouseWrap is manufactured from a polypropylene woven fabric with a polypropylene coating that contains UV inhibitors.

PRODUCT FEATURES & BENEFITS

- Provides protection from water infiltration but breathes allowing water vapor to escape
- Light weight and somewhat translucent to allow for easy installation
- UV resistant and can be left exposed for up to 6 months
- Tear resistant reduces jobsite waste and blow-offs
- Meets and exceeds all current building codes for water resistive barrier as well as air barrier

PRODUCT SPECIFICATIONS			TEST METHOD	ROLL SIZE	ROLLS PER PALLET
Composition	Woven Polypropylene			9' x 100'	50
Weight per Roll	13.1 lbs. / MSF			9' x 150'	45
Thickness	5.5 mils.			9' x 195'	40
Tensile Strength	MD	79	ASTM D5034	10' x 100'	50
	CD	51		10' x 150'	45
Tear Strength	MD	47.1	ASTM D4533	10' x 195'	40
	CD	18.7		54" x 100'	100
Water Resistance	Pass		ASTM D779	54" x 150'	90
MVTR / Perms	9 Perms		ASTM E96	54" x 195'	80
Fire Rating	Class A		ASTM E84	36" x 100'	150
				36" x 150'	135

Scan the QR code
to access additional
information.

