

# **GSPro** lce & Water Protection

SBS Modified Self-Adhering Underlayment



#### **USES AND DESCRIPTION**

TopShield®GSPro Ice & Water is an SBS modified self-adhering membrane reinforced with non-woven fiberglass mat for extra strength and durability.

TopShield®GSPro Ice & Water is a highly versatile underlayment that provides superior waterproof integrity and is an excellent second wall of defense against wind driven rain and seepage due to ice damming.

For use on decks 2:12 and greater.

## **Product Code: TOPGSPIW**

PRODUCT PROPERTIES			
PROPERTIES	REFERENCE TEST	RESULTS	
Maximum Load, min	ASTM D1970	MD=35 CD=35	
Elongation at Break, min	ASTM D1970	30%	
Adhesion to Plywood	ASTM D1970	Pass @ 77° F min = 20.0 lbf/ft	
Thermal Stability	ASTM D1970	0.05	
Flexibility Temperature	ASTM D1970	Pass @ -20° F min	
Nail Sealability	ASTM D1970	Pass	
Waterproof Integrity after Low Temp Flexibility	ASTM D1970	Pass	
Waterproof Integrity of Lap Seam	ASTM D1970	Pass	
Slip Resistance	ASTM D1970	Pass	

#### **BENEFITS**

- Offers a skid resistant, granular surface
- Allows for easy installation and handling as a result of silicone treated split back release film
- Provides high temperature stability
- May be installed directly to concrete, plywood, wood composition board and gypsum
- Self seals around nails
- May be used in new construction or re-roofing
- May be left exposed up to 60 days prior to application of finished roof
- Offers greater tear resistance than traditional felt underlayment
- Provides protection for critical areas such as rakes, eves, valleys, flashings, hips, ridges, dormers and skylights
- Provides excellent low temperature flexibility
- Florida Approval (FL #17401)
- Miami-Dade Approval

PRODUCT DATA		
Properties	Typical Values	
Width	36 in	
Length	65 ft	
Weight	60 lb (±2lbs)	
Thickness	50 mils	
Square Feet	195 sqft	

## **COMPLIANCE CODES**

- Meets the Requirements of ASTM D1970
- U.L. Classified as a Prepared Roofing Accessory
- FBC Approved FL17401
- · Miam-Dade







