

SAFETY DATA SHEET

TopShield® Defender Ice & Water

GHS	PROTECTIVE CLOTHING	TRANSPORT OF DANGEROUS GOODS
Not Regulated	 	Not Regulated

SECTION 1: Product and Company Identification

TRADE NAMES: Acoustidrain, Duolap Cap GR, Flash Stick, High Resistance Cap Sheet Membrane – Single-ply, High Resistance Cap Sheet Membrane – Two-ply, ICF Foundation Waterproofing Membrane, Insono AF3, Lastobond Sanded Finish, Lap Stick, Lastobond HT-N, Lastobond HT-S, Lastobond-Pro LT, Lastobond Pro Grip, Lastobond Smooth Seal HT, TopShield® Defender HT, LB 1236, LB 1244, Multipurpose Aluminum Waterproofing Membrane, Red Zone Waterproofing Membrane, Red Zone 25, Red Zone 25 All Temperatures, Redzone Pro, Resisto Base Sheet Membrane, Resisto Base Sheet Membrane, Resisto SA, Resisto Select, Resisto STT, VB 30, VB50.

USE: Membranes are used for all types of roofing needs, air barrier and waterproofing protection.

DISTRIBUTOR: SRS Distribution, Inc.
7440 STATE HWY 121
McKinney, TX 75070
United States
www.srsdistribution.com
info@srsdistribution.com

TELEPHONE: TECHNICAL
(8:00am to 5:00pm - US Central Time Zone) M-F
214-491- 4149

EMERGENCY
24 hr - CHEMTREC (USA)
1-800-424-9300

SECTION 2: Hazard(s) Identification

Bitumen membrane. Asphalt odour. Under normal use, this product is not expected to create any health or environmental hazard. Inhalation of dust or asphalt fumes can cause respiratory irritation and/or congestion.

SECTION 3: Composition/Information on Ingredients

CHEMICAL NAME	CAS NUMBER	% WEIGHT	EXPOSURE LIMIT (ACGIH)	
			TLV – TWA	TLV – STEL
BITUMINOUS BLEND				
Bitumen ¹	8052-42-4	15-40	0.5 mg/m ³ Asphalt fumes	NE
Oxidized bitumen ¹	64742-93-4	0-20	0.5 mg/m ³ Asphalt fumes	NE
Self-adhesive membranes contain: Highly hydrotreated naphthenic oil ¹	64742-52-5	1-5	Not established	NE
Calcium carbonate ¹	471-34-1	0-30	10 mg/m ³	NE
Styrene butadiene copolymer ¹	9003-55-8	1-5	10 mg/m ³	NE
CHEMICAL NAME	CAS NUMBER	% WEIGHT	EXPOSURE LIMIT	
			TLV – TWA	TLV – STEL
REINFORCEMENT Some products may contain fibre glass, polyester or a mix of glass grid and polyester.				
Polyester mat ¹	N/A	0-7	NE	NE

SAFETY DATA SHEET

TopShield® Defender Ice & Water

CONTINUED: SECTION 3

Fibre glass mat ¹ Contains: Fibre glass filament ¹	N/A 65997-17-3	0-7 0-7	NE 1f/cc	NE NE
UNDERFACE AND SURFACE Some membranes are protected by sand, talc, mineral granule, silicone paper, polyethylene or polypropylene film, aluminium, copper or stainless steel foil.				
Silicone paper	N/A	0-5	NE	NE
Polypropylene film	N/A	0-5	NE	NE
Polyethylene film	9002-88-4	0-5	NE	NE
Aluminium, copper or stainless steel foil	N/A	0-15	NE	NE
1. The exposure to the product above the limits of exposure is not likely to occur considering its form (incorporated in the mixture) and the provided use. The limit of exposure is given for reference only.				

NOTE: NA = Not Available

NE = Not Established

EFFECTS OF SHORT TERM (ACUTE) EXPOSURE

SKIN CONTACT:	The product can cause a mechanical irritation of the skin because of its rough surface. The product may stain and stick to the skin. The contact with this product at high temperature can cause thermal burns.
EYE CONTACT:	The product is not likely to cause effects to the eyes. The contact with this product at high temperature can cause thermal burns.
INHALATION:	The product is not likely to cause effects to the respiratory system. If the membrane is burned, asphalt fumes can be emitted and cause irritations to the nose, the throat and the respiratory tracts, tiredness, headaches, dizziness, nausea, and insomnia.
INGESTION:	Exposure is not likely to occur by this route of entry under normal use of the product.

EFFECTS OF LONG TERM (CHRONIC) EXPOSURE

SKIN CONTACT:	The repeated or prolonged contact can cause irritation. (1)
INHALATION:	Under normal use, the product is not likely to cause effects to the respiratory system.
CARCINOGENICITY:	<p>Due to the product form, exposure to hazardous dusts or fumes is not expected to occur. Information on carcinogenicity is given for reference only. This product is not classifiable as a carcinogen.</p> <p>Bitumen: Asphalt fumes may contain a variety of polycyclic aromatic hydrocarbons (PAH), some of which are associated with the potential of inducing skin cancer. Increasing amounts of PAH may be released if this product is heated above 200°C. Prolonged or repeated contact of PAH with skin may cause skin cancer where poor personal hygiene may be a contributing factor. Asphalt fumes contain substances such as Benzo(a)pyrene and Dibenzo(a,h)anthracene that are known to cause cancer in humans. In its 2013 monograph (Volume 103), the International Agency for Research on Cancer (IARC) conducted a review of the potential carcinogenicity of bitumen (the European term for asphalt). One of its conclusions was that the "occupational exposures to straight-run bitumens and their emissions during road paving are possibly carcinogenic to humans (group 2B)". However, due to the product form, exposure to such component is unlikely under normal conditions of use. (1,2,4)</p> <p>Oxidized bitumen: In its 2013 monograph (Volume 103), IARC conducted a review of the potential carcinogenicity of bitumen (the European term for asphalt). One of its conclusions was "occupational exposures to oxidized bitumens and their emissions during roofing are classified in IARC Group 2A, probably carcinogenic to humans." However, due to the product form, exposure to such component is unlikely under normal conditions of use. (4)</p> <p>Fibreglass filament: Fibreglass is not expected to be released. In October 2001, the IARC classified fibreglass as Group 3 "not classifiable as to its carcinogenicity to humans". The 2001 decision was based on current human and animal researches that showed no association between inhalation exposure to dust from fibreglass wool and the development of respiratory disease. This is a reversal of a study of the American Conference of Governmental Industrial Hygienists (ACGIH) and the National Toxicology Program (NTP) in 1987 that classified the product in Group 2B (possibly carcinogenic to humans). Those results were based on studies in which animals were injected with large quantities of fibreglass.</p>

No information is available about other products.

SAFETY DATA SHEET

TopShield® Defender Ice & Water

CONTINUED: SECTION 3

TERATOGENICITY, EMBRIOTOXICITY, FETOTOXICITY

No information available

REPRODUCTIVE TOXICITY

No information available

MUTAGENICITY

No information available

TOXICOLOGICALLY SYNERGISTIC MATERIALS

No information available

POTENTIAL ACCUMULATION

No information available

SECTION 4: First Aid Measures

SKIN CONTACT If there is presence of dust or stains on the skin, wash gently with water and soap. In the event of contact with the product melted, do not try to remove it from the affected area. Rinse in cold water. Obtain immediate medical attention.

EYE CONTACT Flush eyes with water for at least 15 minutes while holding eyelids open. Do not attempt to remove material from affected area without medical assistance. Obtain immediate medical attention.

INHALATION Remove victim from contaminated place and restore breathing if required.

INGESTION The ingestion of this product is not very likely to occur.

SECTION 5: Fire Fighting Measures

FLAMMABILITY: Not applicable

EXPLOSION DATA: Not applicable

FLASH POINT: Not applicable

AUTO-IGNITION TEMPERATURE: Not applicable

FLAMMABILITY LIMITS IN AIR: (% in volume) Not applicable

FIRE AND EXPLOSION HAZARDS: If the product is heated, take note that asphalt fumes are flammable.

Do not use water on an asphalt fire.

COMBUSTION PRODUCTS: Burning of this material will produce thick black smoke. Irritating and/or toxic gases (including hydrogen sulphide and sulphur dioxide) and traces of metallic fumes may be generated by thermal decomposition or combustion.

FIRE FIGHTING INSTRUCTIONS: Evacuate the area. Wear self-contained breathing apparatus and appropriate protective clothing that are in accordance with standards. Approach fire from upwind and fight it from maximum distance or use unmanned hose holders or monitor nozzles. Always stay away from the containers at the time of the fire considering the high risk of explosion. Move the rolls of membrane from fire area if it can be done without risk. Cool the rolls of membrane with flooding quantities of water until well after fire is out.

EXTINGUISHING MEDIA: Foam, CO₂, sand, and chemical powder.

SECTION 6: Accidental Release Measures

RELEASE OR SPILL: If hot material is spilled, allow enough time to cool completely and place it in a container for disposal. Wear appropriate breathing apparatus (if applicable) and protective clothing. Notify appropriate environmental agencies. Wash spill area with soap and water. Dispose of the material according to local environmental regulations.

SECTION 7: Handling and Storage

HANDLING: Avoid contact with skin, eyes and clothes. Do not ingest. Wash hands after manipulation.

STORAGE: Flashings must be stored in such a way to prevent any creasing, twisting, scratches and other damages of the roof. The materials must be protected adequately and stored permanently away from flames or welding sparks, protected from bad weather and any harmful substances. Self-adhesive membranes must be stored away from the sun.

SAFETY DATA SHEET

TopShield® Defender Ice & Water

SECTION 8: Exposure Controls / Personal Protection

PERSONAL PROTECTIVE EQUIPMENT:



HANDS: Wear resistant gloves.

RESPIRATORY: If the threshold limit value (TLV) for dust is exceeded and if use is performed in a poorly ventilated confined area, use an approved respirator that is in accordance with standards.

EYES: Wear safety goggles that are in accordance with standards.

BODY: Wear adequate protective clothes.

OTHERS: Eye bath and safety shower.

SECTION 9: Physical and Chemical Properties

PHYSICAL FORM: Solid Rolls or Sheets

APPEARANCE/DESCRIPTION: Various film colors, gray adhesive.

PHYSICAL STATE	SOLID
ODOUR AND APPEARANCE	BLACK MEMBRANE WITH ASPHALT ODOUR
ODOUR THRESHOLD	NOT AVAILABLE
VAPOUR PRESSURE (20°C)	NOT APPLICABLE
VAPOUR DENSITY (AIR = 1)	NOT APPLICABLE
EVAPORATION RATE (BUTYL ACETATE = 1)	NOT APPLICABLE
BOILING POINT (760 MM HG)	NOT APPLICABLE
FREEZING POINT	NOT APPLICABLE
SPECIFIC GRAVITY (H ₂ O = 1)	VARIABLE
SOLUBILITY IN WATER (20°C)	NONE
VOLATIL ORGANIC COMPOUND CONTENT (V.O.C.)	NOT MEASURABLE (0 G/L)
VISCOSITY	NOT APPLICABLE

SECTION 10: Stability and Reactivity

STABILITY: This material is stable.

CONDITIONS OF REACTIVITY: Avoid excessive heat.

INCOMPATIBILITY: Avoid strong acids and strong alkalis, oxidizers, organic solvents, and greasy substances

HAZARDOUS DECOMPOSITION PRODUCTS: None identified

HAZARDOUS POLYMERISATION: None

SECTION 11: Toxicological Information

TOXICOLOGICAL DATA

No information is available.

Effects of Short-Term (Acute) Exposure *No information is available.*

SAFETY DATA SHEET

TopShield® Defender Ice & Water

CONTINUED: SECTION 11

Effects of Long-Term (Chronic) Exposure

CARCINOGENICITY

Bitumen: Data from experimental studies on animals and cultured mammalian cells indicate that laboratory-generated roofing asphalt fume condensates are genotoxic and cause skin tumours. (2)
Highly hydrotreated naphthenic oil: No study on the human and the animals made it possible to classify naphthenic oils highly hydrotreated as carcinogen (IARC, 1984). (1)

No information is available about other products.

REPRODUCTIVE EFFECTS

No information available

TERATOGENICITY, EMBRYOTOXICITY, FETOTOXICITY

No information available

MUTAGENICITY

Crystalline silica: No effect according to the information available.

No information available

SECTION 12: Ecological Information

ENVIRONMENTAL EFFECTS

No data available

BIODEGRADABILITY

This product is not biodegradable. There is no possible bioaccumulation and unlikely bioconcentration in the food chain.

SECTION 13: Disposal Considerations

WASTE DISPOSAL

This product is not hazardous waste. Consult local, provincial, territory or state authorities to know disposal methods. This material is not listed by the EPA as hazardous waste according to the **Resource Conservation and Recovery Act (RCRA)** of the United States. No EPA waste numbers are applicable for this product.

SECTION 14: Transport Information

This product is not regulated by the Department of Transportation (DOT) and Transportation Dangerous Goods (TDG).

SECTION 15: Regulatory Information

DSL

All constituents of this product are included in the Domestic Substances List (DSL) of Canada.

TSCA

All constituents of this product are listed on the Toxic Substances Control Act Inventory (TSCA) of the United States.

Prop. 65

Prop. 65: This product contains chemicals known to the State of California to cause cancer or reproductive toxicity.

SECTION 16: Other Information

GLOSSARY

CAS

Chemical Abstract Services

CSA

Canadian Standardization Association

GHS

Globally Harmonized System

LD₅₀/CL₅₀

Less high lethal dose and lethal concentration published

TLV-TWA

Threshold Limit Value – Time-weighted average

SAFETY DATA SHEET

TopShield® Defender Ice & Water

CONTINUED: SECTION 16

References

- (1) Safety Data Sheet from the supplier
- (2) NIOSH (2001) Hazard Review, Health Effects of Occupational Exposure to Asphalt. U.S. Department of Health and Human Service, Centers for Disease Control and Prevention, National Institute for Occupational Safety and Health, DHHS (NIOSH) Publication No. 2001-110.
- (3) CHEMINFO (2010) Canadian Centre of Occupational Health and Safety, Hamilton (Ontario) Canada

Code of SDS

CA U DRU SS FS 043

The Safety Data Sheets of TopShield® products are available on Internet at the following site:
TopShieldProducts.com

Update justification:

- Triennial update

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Revision date: September 3, 2025

