

HYBRID CONSTRUCTION SEALANT

TopShield[®] Hybrid Construction Sealant provides a strong, long lasting bond to PVDF, SMP, and polyester coated steel, bare galvanized, Galvalume metal panels, aluminum, copper, skylights, glass, brick, wood, asphalt shingles, and vinyl siding.





INTERIOR & EXTERIOR

INTABLE WITH MOST LATEX-BASED PAIN SE PUEDE PINTAR CON LA MAYORIA DE LAS PINTURAS A BASE DE LÁTEX

DEAL FOR BRICK, METAL, VINYL & WOU SIDING, CONCRETE, ASPHALT, SHINGLES DEAL PARA LADRILLOS; RECUBRIMIENTOS DE NETIC VINULO Y MADERA; CONCRETO: ASFALLOY TELIS



10.0 FL OZ (295 mL)

Bone White TS384101 Gray Mirage TS384122

Antique Bronze TS384142

> 10 OZ (24 tubes/case)





TS384141

FEATURES

- Long lasting watertight seal won't shrink
- Permanently flexible exciseding rigorous
 ASTM C-920 Class 50 Testing
- Applicable in wet or dry weather conditions down to 0° F
- Strong lasting bond
- Available in multiple colors

FOR USE ON

PVDF, SMP, and polyester coated steel, bare galvanized, galvalume metal panels, aluminum, copper, skylights, glass, brick and block, wood, vinyl siding, and asphalt shingles



Scan the QR code to access additional information.