

SECUREGRIP 30 Synthetic Roof Underlayment

TopShield SecureGrip 30 Synthetic Roof Underlayment is a synthetic roof-deck protection designed and manufactured to replace asphalt saturated felt in sloped roof system construction.



Rightly Engineered

Barrier for your shingle roof system.

Inorganic Construction

Moisture protection - doesn't absorb water and is inert to mold growth.

Advanced Surface Technologies

SecureWalk™ (top) and SecureGrip (back) promotes exceptional walkability.

Improves Project Outcome

Eliminating customer callbacks.

Easier Installation

33% more coverage per pass across the roof (vs 36" wide rolls).

Superior Performance

Designed to perform under extreme weather conditions.

Durable

Synthetic construction resists tearing during roof installation - UV stabilized to resist UV degradation up to 3 months.

Uses

installations of standing seam metal panels.

Storage

Always store rolls upright on pallets (or in the cradled pallet they are shipped on) and in a dry protected area.

Availability

TopShield SecureGrip 30 Synthetic Felts are available throughout the United States. Check with your local representative for product availability.

Compliance: Codes

- Performance characteristics meet or exceed ASTM D4869 – Type I, II, III and IV
- Performance characteristics meet or exceed ASTM D226 – Type I, II
- Tested in accordance with ICC-AC-207- UV Exposure –180 days
- Meets the requirements of ICC-AC-188 – Intertek / WH #CCRR 1045
- FBC Approved - #FL18374
- TDI Listed – CCRR #1045
- Miami-Dade County approved 17-0228.03

PHYSICAL DATA	
Per Roll	48" X 250'
Material Per Roll	1000 sq. ft.
Squares Per Roll	10 squares
Weight Per Roll	24 lbs
Rolls Per Pallet	56 rolls
Wt Per Pallet	1,344 lbs
Limited Warranty	30 Years

SPECIFICATIONS (meets or exceeds applicable standards)		
	Standard	SecureGrip 30
Permeability	ASTM E96	06 perms
Water Transmission	ASTM D4869	Pass
Nail Sealability	ASTM D1970	Pass
Pliability	ASTM D226	Pass
Tear Strength	ASTM D4533	MD 25 lbs / CD 25 lbs
Tensile Strength	ASTM D751	MD 109 lbs / CD 87 lbs
Elongation	ASTM D751	MD 20% / CD 20%
Wt Per Square	ASTM D5261	2.3 lbs
Nominal Thickness	ASTM D5261	7 mils
Range of Temperature	-	- 40°F to 240°F
Fire Rating UL Class A	ASTM E108	Pass



Intertek

Escanearel código QR para acceder adicional información

