## PRODUCT SPECIFICATIONS TS550 ROOF LOUVER

## 1.1 MATERIALS:

- **1.1.1 Aluminum Alloys:** Conform to ASTM B209. Base: 0.019" Aluminum Coiled Sheet. Pan: 0.019" Aluminum Coiled Sheet.
- 1.1.1 Plastic Polymers: Collar: Custom blended, high impact co-polymer with UV stabilization additives. Collar: 0.0175" Aluminum Coiled Sheet.
- **1.1.3** Screen: 10 mil, 8x8 mesh Aluminum Screen.
- **1.1.4 Paint**: Factory applied baked on Valspar Super Flex.

## 1.2 MISCELLANEOUS:

- **1.2.1 Description:** Pan-style, self-flashing roof mounted attic exhaust vent. Features a weathertight collar and large nailing flange. Screen is securely held in place for increased weather and pest protection. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.
- **1.2.2** Color: Available in BROWN, WHITE, BLACK, WEATHERED BRONZE and MILL finish.
- **1.2.3** Net Free Area: 50 square inches per unit.
- **1.2.4** Dimensions: Overall Overall 15<sup>3</sup>/<sub>8</sub>" x 16<sup>3</sup>/<sub>8</sub>" x 3<sup>3</sup>/<sub>4</sub>", Hole Size 9".
- **1.2.5** Packaging: Packaged 6 to a carton. UPC labels are affixed to each vent and carton.
- **1.2.6** Approvals: Texas Department of Insurance "Windstorm" Approved Product Evaluation Report No.: RV-119.

Revised on 8/15/2022



Scan the QR code to access additional information