



TSLOR9-4 Lo-OMNIRIDGE SHINGLE OVER RIDGE VENT

PRODUCT SPECIFICATIONS

1.1 MATERIALS:

1.1.1 Plastic Polymers:

Custom blended, high impact co-polymer with UV stabilization additives.

2. MISCELLANEOUS:

1.2.1 Description:

Injection molded, shingle over ridge vent. Molded in 4 foot sections. Adjustable to roof pitches from 2/12 to 16/12. Features an exterior venturi baffle with perpendicular omni baffles, internal aerodynamic curved baffles, molded end plugs, weather proof under lapping connection with alignment tabs, water shield at the louvers, and fully supported nail holes. Molded nailing lines for cap shingles. For use with 9" cap shingles. This is an exhaust vent and must be used in conjunction with adequate intake vents for proper operation.

1.2.2 Color:

Available BLACK.

1.2.3 Net Free Area:

11 square inches per linear foot. (44 square inches per 4 foot part.)

1.2.4 Packaging:

Packaged 10 to a carton. Available in 4 foot lengths. UPC labels are affixed to each vent and carton.

1.2.5 Warranty:

Limited lifetime warranty.

1.2.6 Performance:

Passed Miami-Dade County test requirements for structural uplift and wind driven rain infiltration.

1.2.7 Approvals:

UL Listed (Class A)-TGEW.R25226

1.2.8 Other:

ICC-ES evaluated - ERS-4531 to follow IBC and IRC standards

Revised on 8/30/2022

Scan the QR code
to access additional
information

