



**9" WIDE FOR ENHANCED
RIDGE CAP SHINGLES**



**Net Free
Area Verified**

TSLOR9-4FR FEATURES

- Sonic welded fiberglass screen provides enhanced weather protection
- Includes 2 1/2" ring shank nails, 30 nails per piece
- Pneumatic nail gun or hammer installed
- Four drain holes per side per foot
- 11 square inches of Net Free Area per linear foot
- External venturi baffle
- Nail holes marked every 6 inches - supported every foot
- Preformed to 3/12 pitch
- Fits roof pitches 2/12 to 16/12
- Molded nail lines
- Molded centerline for fast and easy alignment
- Alignment tabs
- External water shield
- Slot width guide lines
- Patented molded-in fanfolded endplug fits all roof pitches
- **Lifetime Limited Warranty**

1. Full UL mark included on vent
2. Aerodynamically curved internal baffles to minimize wind resistance
3. Unique OmniRidge[®] perpendicular baffles enhance airflow
4. Louvers positioned closer to wind stream for better airflow
5. Molded-in endplug
6. Weatherproof under-lapping joint prohibits weather infiltration

SPECIFICATIONS		
Model	Packaged	
TSLOR9-4FR	10 Per Box	
Length (ft.)	Roof Pitch (in.)	NFA (in. ²)
4	2/12 to 16/12	44

Revised on 8/21/2022

Scan the QR code
to access additional
information

