

TSPRO4-SNW FEATURES

- Advanced low profile design
- Includes 2 ½" ring shank nails, 30 nails per piece
- Anti-rotation base design
- Internal baffles
- External "Omni" baffles
- External Venturi baffle
- "Posi-tabs" contour to shingles for improved weather protection
- Weatherproof underlapping joints
- 6 drain holes per side per foot
- 18 square inches of Net Free Area per linear foot
- 10 supported nail holes
- Preformed to 2/12 pitch
- Fits roof pitches 2/12 to 16/12
- Molded-in shingle nail lines, reinforced every 2 inches
- Slot width guide lines
- Continuous molded end plug for improved weather protection
- Lifetime Limited Warranty

- **1.** External Venturi and "Omni" baffles provide enhanced airflow
- 2. Fully supported nail holes
- **3.** Sonic welded fiberglass screen provides enhanced weather protection
- **4.** Unique "posi-tabs" contour to shingles for improved weather protection
- **5.** Continuous molded end plug and underlap prohibit weather infiltration

SPECIFICATIONS		
Model	Packaged	
TSPRO4N	10 Per Box	

Length	Roof Pitch	NFA
(ft.)	(in.)	(in.²)
4	2/12 to 16/12	

Revised on 9/9/2022

Scan the QR code to access additional information

