

TopShield®PRO SEAM and REPAIR TAPE - Black 12" x 50'

SECTION 1: Product and Company Identification

MATERIAL NAME: TopShield®PRO Seam and Repair Tape – Black 12"x50'

CHEMICAL CATEGORY: Article

PRODUCT CODE: TS-Seam12-BK

PRODUCT USE: Metal Roof Flashing Product

DISTRIBUTOR: APOC

4161 E. 7TH AVENUE TAMPA, FL 33605 UNITED STATES

TELEPHONE

TECHNICAL: 813-248-2101 **EMERGENCY: 800-424-9300**

LAST REVISION DATE: 1/11/2018

SECTION 2: Hazards Identification

SIGNAL WORD-NONE GHS HAZARDS AND PRECAUTIONS

The mixture does not meet the criteria for classification.

PREVENTION: Observe good industrial hygiene practices.

RESPONSE: Wash hands after handling.

STORAGE/DISPOSAL: Store away from incompatible materials. Dispose of waste and residuesin accordance with local authority requirements.

GHS HAZARD SYMBOL - NOT REQUIRED

PHYSICAL FORM:

COLOR:

Multiple

ODOR:

FLASH POINT:

OSHA(HCS2012):

WHMIS:

GHS:

Solid Tape

Multiple

A28°F(220°C)

Not classified.

Not classified.

Not classified.

ROUTE OF ENTRY: Inhalation, Skin, Eye, Ingestion/Oral MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not Classified

POTENTIAL HEALTH EFFECTS

INHALATION

ACUTE (Immediate): Expected to be a low ingestion hazard.

CHRONIC (Delayed): Not Classified

SKIN

ACUTE (Immediate): No adverse effects due to skin contact are expected.

CHRONIC (Delayed): This product is not expected to cause skin sensitization.

EYE

ACUTE (Immediate): Direct contact with eyes may cause temporary irritation.

CHRONIC (Delayed): Not Classified

INGESTION

ACUTE (Immediate): Not Classified CHRONIC (Delayed): No data available

CARCINOGENIC EFFECTS: This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.



TopShield®PRO SEAM and REPAIR TAPE - Black 12" x 50'

SECTION 3: Composition/Information on Ingredients

Chemical Name	CAS#	%(wt)	UN;EINECES	LD50/LC50	Classifications According to Regulation/Directive	Other
Talc (Powder)	14807-96-6	10-<20%				NDA
Other Components	1332-58-7	10-<90%				NDA

This product is an encapsulated mixture which reduces the likelihood of exposure particulates.

See Section 11 for Toxicological Information

SECTION 4: First Aid Measures

Inhalation: Move to fresh air. Call a physician if symptoms develop or persist.

Skin: Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye: Rinse with water. Get medical attention if irritation develops and persists.

Ingestion: Rinse mouth. Get medical attention if symptoms occur.

Other Information: Direct contact with eyes may cause temporary irritation. Ensure that medical personnel are aware of the

material(s) involved, and take precautions to protect themselves.

See Section 2 for Potential Health Effects.

SECTION 5: Fire Fighting Measures

EXTINGUISHING MEDIA: Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

UNSUITABLE EXTINGUISHING MEDIA: Do not use water jet as an extinguisher, as this will spread the fire.

FIREFIGHTING PROCEDURES: Use water spray to cool unopened containers. Use standard firefighting procedures and consider the hazards of other involved materials.

UNUSUAL FIRE AND EXPLOSION HAZARDS: No unusual fire or explosion hazards noted.

HAZARDOUS COMBUSTION PRODUCTS: During fire, gases hazardous to health maybe formed.

PROTECTION OF FIREFIGHTERS FLASH POINT: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental Release Measures

PERSONAL PRECAUTIONS: Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

EMERGENCY PROCEDURES: Keep unnecessary personnel away.

ENVIRONMENTAL PRECAUTIONS: Avoid discharge into drains, water courses or onto the ground.

CONTAINMENT/CLEAN-UP MEASURES: No Information Available

PROHIBITED MATERIALS: None listed

SECTION 7: Handling and Storage

HANDLING: Avoid prolonged exposure. Observe good industrial hygiene practices.

STORAGE: Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

INCOMPATIBLE MATERIALS OR IGNITION SOURCES: No Listing

SECTION 8: Exposure Controls / Personal Protection

PERSONAL PROTECTIVE EQUIPMENT PICTOGRAMS:

RESPIRATORY: wear suitable respiratory equipment.

EYE/FACE: Wear safetyglasses with side shields (or goggles).

HANDS: Wear appropriate chemical resistant gloves.

 $\textbf{SKIN/BODY:} \ We ar suitable \ protective \ clothing.$

PICTOGRAMS:



GENERAL INDUSTRIAL HYGIENE: Always observe good personal hygiene measures, such as washing after handling considerations the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. ENGINEERING MEASURES/CONTROLS: Good general ventilation (typically10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.



TopShield®PRO SEAM and REPAIR TAPE – Black 12" x 50'

EXPOSURE LIMITS/GUIDELINES: Refer to listed exposure limits in state information of this section.

EXPOSURE LIMITS/GUIDELINES					
	Result	ACGIH	NIOSH	OSHA	
Talc(powder) CAS-14807-96-6	TWAs	2mg/m3TWA(respirablefraction)	2mg/m3TWA(respirable fraction)	0.3mg/m3 Total Dust 0.1mg/m3 Respirable 20mppcf 2.4 mppcf Respirable	

SECTION 9: Physical and Chemical Properties

PHYSICAL FORM: Solid Rolls or Sheets

APPEARANCE/DESCRIPTION: Various film colors, gray adhesive.

COLOR:	Various Film colors, gray adhesive	ODOR:	Slight
TASTE:	No Data Available	ODOR THRESHOLD:	NDA
BOILING POINT:	NDA	VAPOR PRESSURE:	N/A
MELTING POINT:	NDA	VAPOR DENSITY:	N/A
SPECIFIC GRAVITY/ RELATIVE DENSITY:	1.04 Estimated	EVAPORATION RATE:	N/A
AUTO-IGNITION TEMPERATURE:	>842 F (>450 C)	VOC (Wt.):	NDA
BULK DENSITY:	NDA	VOC (Vol.):	NDA
SOLVENT SOLUBILITY:	NDA	FLASH POINT:	428°F (220°C)
VISCOSITY:	NDA	FLASH POINT TEST:	NDA

SECTION 10: Stability and Reactivity

STABILITY: Stable under normal conditions

HAZARDOUS POLYMERIZATION: Hazardous polymerization not indicated.

CONDITIONS TO AVOID: Avoid temperatures exceeding the flash point. Contact with incompatible materials.

INCOMPATIBILE MATERIALS: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: No hazardous decomposition products are known.

Concentration

SECTION 11: Toxicological Information

Component Name

Component Name	Concentration	CAS	Data		
Talc (powder)	10-<20%	14807-96-6			
IARC MONOGRAPHS. Overall Evaluation of Carcinogenicity		2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans.			
OTHER INFORMATION		(Talc) Prolonged skin contact may cause temporary irritation.			
REPRODUCTIVE TOXICITY		This product is not expected to cause reproductive or developmental effects.			
SPECIFIC TARGET ORGAN TOX	ICITY - Single Exposure	Not classified.			
SPECIFIC TARGET ORGAN TOX	ICITY - Repeated Exposure	Not classified.			
ASPIRATION HAZARD		Not available.			
CHRONIC EFFECTS		Prolonged inhalation may be harmful.			

CAS

Data



TopShield®PRO SEAM and REPAIR TAPE - Black 12" x 50'

SECTION 12: Ecological Information

ECOLOGICAL FATE	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
PERSISTENCE/DEGRADABILITY	No data is available on the degradability of this product.		
BIOACCUMULATION POTENTIAL	No data available.		
MOBILITY IN SOIL	No data available.		
OTHER ADVERSE EFFECTS	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

SECTION 13: Disposal Considerations

PRODUCT	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations. The waste code should be assigned in discussion between the user, the producer and the waste disposal company. Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
PACKAGING	Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

SECTION 14: Transport Information

D.O.T. - UNITED STATES - DEPARTMENT OF TRANSPORTATION: Shipping Name: Not Regulated as Dangerous Goods.

IATA - INTERNATIONAL AIR TRANSPORT ASSOCIATION: Shipping Name: Not Regulated as Dangerous Goods.

IMO/IMDG - INTERNATIONAL MARITIME TRANSPORT: Shipping Name: Not Regulated as Dangerous Goods.

SECTION 15: Regulatory Information

SARA Hazard Classifications	Not Classified
Risk & Safety Phrases	All components are on the U.S. EPA TSCA Inventory List. This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not Regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)	Not Regulated.
SARA 304 Emergency release notification	Not Regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not Regulated.
SARA 302 Extremely Hazardous Substance	Not Listed.
SARA 311/312 Hazardous	No.



TopShield®PRO SEAM and REPAIR TAPE – Black 12" x 50'

SARA 313 (TRI Reporting)	Not Regulated.
Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List	Not Regulated.
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)	Not Regulated.
Safe Drinking Water Act US. California Proposition 65	Not Regulated. Titanium Dioxide is listed due to its respirable nature in powder form. As supplied and applied the titanium dioxide is bound within the product matrix and is not expected to be in a respirable form. WARNING: This product contains a chemical known to the State of California to cause cancer.

CTATE DIGITTO KNOW	Component Name	CAS	MA	MN	NJ	PA
STATE RIGHT TO KNOW	Talc (powder)	14807-96-6	Yes	NA	Yes	Yes

SECTION 16: Other Information

LAST REVISION DATE: 1/11/2018

PREPARED BY: GG Inc.

DISCLAIMER/STATEMENT OF LIABILITY: This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. APOC does not accept liability for any loss or damage that may occur from the use of this information.

Scan QR Code for additional information.

