

#33 All Weather Rubberized Cement

DATA SHEET

FOR PROFESSIONAL USE ONLY

COMPLIANCE: Exceeds performance requirements of ASTM D3409 and ASTM D4586, TYPE I. Miami-Dade County Product Control Approved.

DESCRIPTION: Use TopShield PRO #33 All Weather Rubberized Cement with mod-bit membranes, base and ply sheets, as well as for seams, flashings and repairs on SBS modified membranes. Manufactured with top quality asphalt, rubber, fibers and solvents, TopShield PRO #33 features superior durability, adhesion, elongation and recovery. Not for use on APP, TPO, EDPM, PVC or other single ply membranes.

NOTE: This product is formulated for repairs and seams on SBS and APP Modified Roll Roofing Sheets. DO NOT use on TPO, EPDM, PVC or other single ply membranes.

PREPARATION: All surfaces must be clean, have proper drainage and free of surface rust, dust and any other foreign matter. Excessive particulate surfacing materials on modified membranes must be removed (sweeping with a stiff broom is recommended) prior to application. After a minimum of 45 days cure time, apply a reflective roof coating. This will greatly extend the life of the cement.

FOR BEST RESULTS: Immediately after application, embed ceramic granules to match existing roof and provide UV protection. Alternately, allow cement to cure a minimum of 90 days and apply compatible reflective coating. Apply when surface temperatures are between 40 °F and 120 °F. In colder weather, product should be stored in heated room (65 °F to 80 °F) at least 24 hours prior to application. Product formulated for year round use.

APPLICATION: For exterior use only. Protective clothing, gloves, and eyewear should be used during application of this product. Apply with trowel or putty knife. Work material to an even consistency over and into the area to be repaired. Using the "3-course" method, apply cement 1/8" thick, two or three inches beyond the problem area. Then reinforce the repair and embed a strip of polyester, fiberglass or cotton reinforcing fabric. Brush fabric to ensure it is fully saturated from the bottom side up. Finally, cover the fabric with an additional layer of cement. Form a feathered edge with cement where chimneys, vent pipes, and other projections meet the roof line. For best results, protect completed repair with a reflective coating.

COVERAGE RATE: Approximately 12 1/2 sq. ft. per gallon when applied 1/8" thick.

STORAGE & HANDLING PRECAUTIONS: When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not store at temperatures above 110 °F. This manufacturer also disclaims liability for flat surface application where poor drainage or moisture may prevail.

CLEAN-UP: Clean tools with paint thinner or mineral spirits.

TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS:

Weight Per Gallon	8.0 - 9.0 lbs.
Consistency	Trowel
Application Temperatures	35 °F - 120 °F
Clean-up Tools	Paint Thinner, Mineral Spirits

Approx. Shipping Weights: (Note: All approx. weights include container)

10.1 oz. tube (300 ml)	0.75 lbs.
1 gallon (3.8L)	9 lbs.
3 gallons (11.4L)	27 lbs.
5 gallons (18.9L)	45 lbs.
55 gallons (208.2L)	505 lbs.

VOC: <250 g/L (regulatory)

WARRANTY AND DISCLAIMER: SRS Distribution, Inc. (herein SRS) hereby warrants to the original purchaser, contingent upon original proof of purchase, that this product will be free from any and all manufacturing defects that may materially and adversely affect the product's performance at the time the product is manufactured. Should a manufacturing defect materially and adversely affect this product's performance, SRS shall, within its sole discretion and upon receipt of Purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product. THIS LIMITED WARRANTY IS PURCHASER'S SOLE AND EXCLUSIVE WARRANTY AND REPLACES ALL OTHER WARRANTIES, CONDITIONS, REPRESENTATIONS AND GUARANTEES, WHETHER EXPRESS OR IMPLIED, WHETHER BY STATUTE, AT LAW OR IN EQUITY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. This limited warranty does not cover labor or installation costs, leaks, or materials not manufactured by OEM supplier, consequential damages or incidental damages. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Direct all warranty claims in writing along with original proof of purchase to TopShield PRO, c/o Warranty Claims Department, 7440 State Highway 121, McKinney, TX 75070-2196. The exclusive venue for any legal action arising out of the purchase of this product or this warranty shall be had in a court of competent jurisdiction within Hillsborough County, Florida. Florida law shall govern. For additional Standard Limited Warranty information contact SRS at (855) 569-1550 or at info@srstopshield.com.