

#81 BUTTER GRADE MASTIC



| TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS | |
|--|-----------------------|
| Weight Per Gallon | 12.3 - 12.8 lbs./gal. |
| Color | White |
| Tensile Strength | 300 psi |
| Elongation | 500% |
| Tool Application | Trowel or Brush |
| Skin Time (50% Relative Humidity, 70 °F) | 30 min |
| Full Cure 1/4" (50% Relative Humidity, 70 °F) | 3 - 7 days |
| Application Temperatures | 40 °F - 110 °F |
| Flash Point | > 450 °F |
| Clean-up Tools | Xylene |

*Specification data may vary +/- 5% from published values

| Approx. Shipping Weights (Note: All approx. weights include container) | |
|--|----------------------|
| 2 gallons (18.9L) | 27.5 lbs. |
| voc | <10 g/L (regulatory) |

FOR PROFESSIONAL USE ONLY

DESCRIPTION: Use TopShield® PRO #81 Butter Grade Mastic for repairs in roofing and waterproofing applications such as in sealing flashings, curbs, penetrations and seams. This 100% silicone repair product has excellent adhesion and flexibility along with chemical, UV and weather resistance.

APPLICATION: For exterior use only. **TopShield® PRO #81** can be applied using a brush, trowel or bulk caulking gun. This product is ideal for almost any sealant or repair application. Surfaces must be clean, dry and free from grease and oils prior to application. Damp or wet surfaces will result in adhesion issues or blisters. Metals must be degreased with a suitable solvent. For best results, apply when air and surface temperatures are 40 °F and rising. Apply at a rate of 12.5 sq. ft. per gallon. Three coursing is recommended on all repairs. Roofing granules may be embedded in top layer of sealant for aesthetics. Skins over in 1 - 2 hours and fully cures in 24 - 36 hours at 70 °F & 50% relative humidity. Lower humidity, thicker films, poor air flow and lower temperatures will increase dry times. This product is designed to be used with silicone based coatings. Because it is a silicone based patching compound, other chemistries such as acrylic will not bond to this product. Verify compatibility prior to coating.

STORAGE & HANDLING PRECAUTIONS: DO NOT allow product to freeze. Protective clothing, gloves, and eyewear should be used during application of these products. When transporting this product, ensure that lid is tight and pail secure and upright. DO NOT allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Seal container when not in use.

CLEAN-UP: Clean tools with xylene. throughout the United States. Check with your local representative for product availability.



#81 BUTTER GRADE MASTIC

WARRANTY AND DISCLAIMER: SRS Distribution, Inc. (herein SRS) hereby warrants to the original purchaser, contingent upon original proof of purchase, that this product will be free from any and all manufacturing defects that may materially and adversely affect the product's performance at the time the product is manufactured. Should a manufacturing defect materially and adversely affect this product's performance, SRS shall, within its sole discretion and upon receipt of Purchaser's timely written notice within the Warranty Period, provide replacement product(s) or refund the purchase price of the defective product.

THIS LIMITED WARRANTY IS PURCHASER'S SOLE AND EXCLUSIVE WARRANTY AND REPLACES ALL OTHER WARRANTIES, CONDITIONS, REPRESENTATIONS AND GUARANTEES, WHETHER EXPRESS OR IMPLIED, WHETHER BY STATUTE, AT LAW OR IN EQUITY, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

This limited warranty does not cover labor or installation costs, leaks, or materials not manufactured by OEM supplier, consequential damages or incidental damages. Some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Direct all warranty claims in writing along with original proof of purchase to TopShield PRO, c/o Warranty Claims Department, 7440 State Highway 121. McKinney, TX 75070-2196. The exclusive venue for any legal action arising out of the purchase of this product or this warranty shall be had in a court of competent jurisdiction within Hillsborough County, Florida. Florida law shall govern. For additional Standard Limited Warranty information contact SRS at (855) 569-1550 or at info@srstopshield.com.

©2021 TopShield® PRO Manufactured For: SRS Distribution, Inc. 7440 State Hwy 121 McKinney, TX 75070 See SDS for more information

> Scan the QR code to access additional information

