

TopShield®PRO #85 WHITE SILICONE COATING

SECTION 1: Product and Company Identification

MATERIAL NAME: PRODUCT CODE: PRODUCT DESCRIPTION: PRODUCT USE: PRODUCT USE SYNONYM	TopShield®PRO #85 White Silicone Coating TS-8501, TS-8505 White Liquid White Elastomeric Roof Coating S: White Roof Membrane
MANUFACTURER:	APOC 4701 E. 7th AVENUE TAMPA, FL 33605 UNITED STATES
TELEPHONE Technical: <u>Emergency</u> : <u>Emergency</u> :	813-248-2101 800-424-9300 703-5273887
	1/19/2018 1/19/2018

SECTION 2: Hazards Identification

EMERGENCY OVERVIEW

WARNING

	Causes mild skin irritation. Harmful if swallowed.
PREVENTION:	Do not handle until all safety precautions have been read and understood. Use personal protective
	equipment as required. Wash thoroughly after handling.
RESPONSE:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to
	do. Continue rinsing. If skin irritation occurs: Get medical advice/attention.
STORAGE/DISPOSAL:	Store in a closed container. Do not allow product to freeze. Dispose of content and/or container in
	accordance with local, regional, national, and/or international regulations.



CLASSIFICATION:	PRECAUTIONS FOR SAFE HANDLING:
Eye irritation, Category 2A	P102 Keep out of the reach of children
Skin sensitization, Category 1	P201 Obtain special instructions before use
Carcinogenic, Category 2B	P202 Do not handle until all safety precautions have been read and understood
STATEMENTS OF HAZARD: Warning H319 Causes serious eye irritation H317 May cause allergic skin reaction H351 Suspected of causing cancer	P261 Avoid breathing vapors or mists P264 Wash hands thoroughly after handling P272 Contaminated work clothing should not be allowed out of the workplace P281 Use personal protective equipment as required



TopShield®PRO #85 WHITE SILICONE COATING

CAUTION - May cause eye and skin irritation on contact.

PHYSICAL FORM:	Liquid
COLOR:	White Liquid
ODOR:	Paint-Like Odor
FLASH POINT:	185 F(85 C)
OSHA:	Irritant
WHMIS:	Class D - Poisonous and Infectious Materials - Division 2 - Subdivision B
	$\overline{\mathbf{T}}$
GHS:	* Skin Corrosion/Irritation - Category 1, Serious Eye Damage, Eye Irritation - Category 2A

Carcinogenic – Category 2B

NFPA:



POTENTIAL HEALTH EFFECTS

INHALATION	
ACUTE (Immediate):	* Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.
CHRONIC (Delayed):	* Under normal conditions of use, no health effects are expected.
SKIN	
ACUTE (Immediate):	* May cause irritation.
CHRONIC (Delayed):	* Repeated and prolonged exposure to the skin may cause dermatitis.
EYE	
ACUTE (Immediate):	* Likely to cause eye irritation, burning, tearing, etc. on contact with the eyes. If swelling and irritation persist, seek medical attention.
CHRONIC (Delayed):	* Direct contact may cause slight to moderate irritation.
INGESTION	
ACUTE (Immediate):	* May cause irritation. May affect the nervous system. May be harmful or fatal if swallowed.
CHRONIC (Delayed):	* Repeated and prolonged exposure may cause gastrointestinal disturbances including diarrhea, nausea, and vomiting.

CARCINOGENIC EFFECTS			
CAS# IARC NTP			
Titanium Dioxide	13463-67-7	Group 2B-Possible Carinogen	Evidence of Carcinogenicity

SECTION 3: Composition/Information on Ingredients

	Hazardous Components				
CHEMICAL NAME	IDENTIFIERS	%(WEIGHT)	LD50/LC50	CLASSIFICATIONS ACCORDING TO REGULATION/DIRECTIVE	
Dimmethyl Polysiloxe	CAS: 70131-67-8	40.0 - 50.0%	LD50 Oral - rat - > 62.080 mg/kg		
Silica Quartz	CAS: 68476-25-5	30.0 - 40.0%			
Methyltrimethyl Siloxane	CAS: 1185-55-3	2.0 - 5.0%	LD50 Oral, rat = 12,500 mg/kg		
Titanium Dioxide	CAS: 13463-67-7	4.0 - 8.0%	LD50 Oral, rat · 60 gm/kg		



TopShield[®]PRO #85 WHITE SILICONE COATING

		Non-Haza	rdous Components	
CHEMICAL NAME	IDENTIFIERS	%(WEIGHT)	LD50/LC50	CLASSIFICATIONS ACCORDING TO REGULATION/DIRECTIVE

This product is an encapsulated mixture which reduces the likelihood of exposure particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

SECTION 4: First Aid Measures

Inhalation: * IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If signs/ symptoms continue, get medical attention.

Skin: * IF ON SKIN: Rinse skin immediately with plenty of water for 15-20 minutes. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

Eye: * IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion: * IF SWALLOWED: Do not induce vomiting: seek medical advice immediately and show this container or label.

SECTION 5: Fire Fighting Measures

EXTINGUISHING MEDIA: LARGE FIRE: Water spray, fog or regular foam. SMALL FIRES: Dry chemical, CO2, water spray or regular foam. UNSUITABLE EXTINGUISHING MEDIA: No data available.

FIREFIGHTING PROCEDURES: Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Keep unauthorized personnel away.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Product containers may rupture when exposed to extreme heat. Precautions should be taken to prevent release of materials.

HAZARDOUS COMBUSTION PRODUCTS: Non-combustible, substance itself does not burn but may decompose upon heating to produce toxic fumes.

PROTECTION OF FIREFIGHTERS: Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.

FLASH POINT: > 185 F(85 C) CC (Closed Cup)

SECTION 6: Accidental Release Measures

PERSONAL PRECAUTIONS: Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. EMERGENCY PROCEDURES: Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up.

ENVIRONMENTAL PRECAUTIONS: Avoid run off to waterways and sewers.

CONTAINMENT/CLEAN-UP MEASURES: Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use appropriate Personal Protective Equipment (PPE)

PROHIBITED MATERIALS: Avoid contact with strong oxidizing agents and acids.

SECTION 7: Handling and Storage

HANDLING: KEEP OUT OF THE REACH OF CHILDREN! Keep containers tightly closed when not in use. STORAGE: Avoid extreme temperatures and freezing. Keep container/package tightly closed and in a well-ventilated place. SPECIAL PACKAGING MATERIALS: Not Applicable. INCOMPATIBLE MATERIALS OR IGNITION SOURCES: Avoid contact with strong oxidizing agents and acids.

SECTION 8: Exposure Controls / Personal Protection

PERSONAL PROTECTIVE EQUIPMENT PICTOGRAMS:





RESPIRATORY: When used with adequate ventilation, a respirator is not normally required. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge or supplied air respirator. This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

Page 3 of 5



TopShield[®]PRO #85 WHITE SILICONE COATING

EYE/FACE: Wear ANSI approved safety glasses with side shields or safety goggles.

HANDS: Wear chemical resistant gloves with repeated or prolonged exposure.

ENGINEERING MEASURES/CONTROLS: Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable threshold limit values. Use precaution to protect building intake from fumes and vapors created outdoors.

	EXPOSURE LIMITS/GUIDELINES				
	Result	Canada Ontario	Mexico	NIOSH	OSHA
Titanium Dioxide (13463-67-7)	TWAs	10 mg/m ³ TWAEV (total dust)	10 mg/m ³ TWA (as Ti)	10 mg/m ³ TWA	15 mg/m ³ TWA (total dust)

SECTION 9: Physical and Chemical Properties

MATERIAL DESCRIPTION				
Physical Form	Liquid	Appearance/Description	White liquid with heavy consistency.	
Color	White Liquid	Odor	Paint-Like Odor	
Taste	No data available	Particulate Type	Not relevant	
Particulate Size	Not relevant	Aerosol Type	Not relevant	
Odor Threshold	No data available			
GENERAL PROPERTIES	·			
Boiling Point	>300 F	Melting Point	No data available	
Decomposition Temperature	No data available	Heat of Decomposition	Not relevant	
рН	8 @ 25 C(77 F)	Specific Gravity/Relative Density	1.33 Water=1	
Density	11.10 lbs/gal @ 25 C(77 F)	Bulk Density	No data available	
Water Solubility	Soluble 0 % @ 25 C(77 F)	Solvent Solubility	Not relevant	
Viscosity	4,000 cps. @ 25 C(77 F)			
VOLATILITY	^ 	^		
Vapor Pressure	5.3 mmHg (torr) @ 20 C(68 F)	Vapor Density	> 1 Air=1	
Evaporation Rate	< 0.7 Ether = 1	VOC (Wt.)	No data available	
VOC (Vol.)	10 g/L	Volatiles (Wt.)	No data available	
Volatiles (Vol.)	No data available			
FLAMMABILITY				
Flash Point	185 F(85 C)	Flash Point Test Type	CC (Closed Cup)	
UEL	No data available	LEL	No data available	
Autoignition	No data available	Self-Accelerating Decomposition Temperature (SADT)	Not relevant	
Heat of Combustion (Δ Hc)	Not relevant	Burning Time	Not relevant	
Flame Duration	Not relevant	Flame Height	Not relevant	
Flame Extension	Not relevant	Ignition Distance	Not relevant	
ENVIRONMENTAL				
Half-Life	Not relevant	Octanol/Water Partition coefficient	Not relevant	
Coefficient of Water	Not relevant	Bioaccumulation Factor	Not relevant	



TopShield[®]PRO #85 WHITE SILICONE COATING

Bioconcentration Factor	Not relevant	Biochemical Oxygen Demand BOD/BOD5	Not relevant
Chemical Oxygen Demand	Not relevant	Persistence	Not relevant
Degradation	Not relevant		

SECTION 10: Stability and Reactivity

STABILITY: * Stable under normal temperatures and pressures.
HAZARDOUS POLYMERIZATION: * Hazardous polymerization not indicated.
CONDITIONS TO AVOID: * Excessive heat and freezing.
INCOMPATIBILE MATERIALS: * Strong oxidizers and acids.
HAZARDOUS DECOMPOSITION PRODUCTS: * No known issues under normal usage conditions.

SECTION 11: Toxicological Information

Component Name	CAS	Data
Dimmethyl Polysiloxe	70131-67-8	Acute Toxicity: LD50 Oral - rat - > 62.080 mg/kg
Methyltrimethyl Siloxane	1185-55-3	Acute Toxicity: LD50 Oral, rat = 12,500 mg/kg
Titanium Dioxide	13463-67-7	Acute Toxicity: LD50 Oral, rat · 60 gm/kg
Aminopropyl Trimethoxy Silane	13822-56-5	Acute Toxicity: LD50 Oral - rat - > 62.080 mg/kg

OTHER COMPONENT INFORMATION IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz. NTP has listed the following chemicals in this product as known human carcinogens: Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

SECTION 12: Ecological Information

ECOLOGICAL FATE	No Data Available.
PERSISTENCE/DEGRADABILITY	No Data Available.
BIOACCUMULATION POTENTIAL	No Data Available.
MOBILITY IN SOIL	No Data Available.
OTHER INFORMATION	* Do not allow product exposure to the ground or into any waterway. Do not allow entry into muncipal sewer systems.

SECTION 13: Disposal Considerations

PRODUCT

Dispose of content and/or container in accordance with local, regional, national, and/ or international regulations.

SECTION 14: Transport Information

DOT - United States - Department of Transportation - Shipping Name: Not Regulated. TDG - Canada - Transportation of Dangerous Goods - Shipping Name: Not Restricted. IMO/IMDG - International Maritime Transport Shipping Name: Not Regulated. IATA - International Air Transportation Association - Not Regulated.



SAFETY DATA SHEET TopShield®PRO #85 WHITE SILICONE COATING

SECTION 15: Regulatory Information

SARA Hazard Classifications	Acute, Chronic
-----------------------------	----------------

STATE	Component Name	CAS	MA	MN	NJ	PA
	Dimmethyl Polysiloxe	70131-67-8	No	No	Yes	Yes
RIGHT	Silica Quartz	68476-25-5	No	No	Yes	Yes
TO KNOW	Methyltrimethyl Siloxane	1185-55-3	No	No	No	No
	Titanium Dioxide	13463-67-7	Yes	Yes	Yes	Yes
	Component Name	CAS	EU EI	NECS	TS	CA
	Dimmethyl Polysiloxe	70131-67-8	Y	es	Ye	es
INVENTORY	Silica Quartz	68476-25-5	Yes		Ye	es
	Methyltrimethyl Siloxane	1185-55-3	Y	Yes		es
	Titanium Dioxide	13463-67-7	Y	es	Ye	es

Canada

- L	a	b	O	r

Canada - WHMIS - Classifications of Substances				
Dimmethyl Polysiloxe	70131-67-8	45%	D2B	
Silica Quartz	68476-25-5	34%	D2B	
Methyltrimethyl Siloxane	1185-55-3	3%	D2B	
Titanium Dioxide	13463-67-7	6%	D2B	

United States

Liiviioiiiieitt					
U.S CERCLA/SARA - Hazardous Substances and their Reportable Quantities					
Silica Quartz	68476-25-5	34%			
Polydimethyl Siloxane	63148-62-9	10%			
Methyltrimethyl Siloxane	1185-55-3	3%			

United States - California

Environment			
	U.S California - Proposition 65 - Care	inogens List	
Titanium Dioxide	13463-67-7	6%	

Other Information WARNING: This product contains a chemical known to the State of California to cause cancer.

SECTION 16: Other Information

PREPARATION DATE: 1/19/2018

LAST REVISION DATE: 1/19/2018

DISCLAIMER/STATEMENT OF LIABILITY: This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to verify the suitability and completeness of such information for particular use. The manufacturer does not accept liability for any loss or damage that may occur from the use of this information.

